



**CLEMCO**  
The Performance System

**TECHNICAL DATA SHEET**

*Note: For safe, efficient blasting, read and follow the owner's manual and seek training for everyone who will use this equipment.*

**Purpose**

The Clemco nylon quick-coupling nozzle holders attach to any blast hose fitted with quick couplings and hold the blast nozzle in place during blasting.

**Description of Operation**

The operator applies a quarter turn to attach the quick coupling to any blast hose fitted with standard blast hose quick couplings. A lock-spring on the nozzle holder keeps the holder from coming uncoupled when attached to any Clemco coupling. The coupling gasket serves as the nozzle washer.

**Nozzles**

- CFPM accepts a 1-inch or 1 1/4-inch entry contractor thread nozzle
- CFP accepts a 1-inch entry, 1 1/4-inch thread nozzle
- FHP accepts a 1 1/4-inch entry flanged nozzle

**Advantages**

- Fiber-reinforced nylon material springs back from most impacts that would dent or deform metal couplings
- Built-in lock-springs eliminate need for safety pins
- Quick-coupling holders can attach to any coupled hose, simplifying blast hose inventory
- Lighter weight than metal nozzle holders

**Description**

Fiber-reinforced nylon quick coupling nozzle holder for abrasive blast cleaning.



**CFPM Nozzle Holder, Stock No. 07719**  
(For contractor thread nozzles)  
Shown with optional nozzle

**Nylon Quick Coupling Nozzle Holders**

Stock Nos. 07716, 07718, 07719



**CFP Nozzle Holder, Stock No. 07716**  
(For 1 1/4" thread nozzles)  
Shown with optional nozzle



**FHP Nozzle Holder, Stock No. 07718**  
(For flanged nozzles)  
Shown with optional nozzle

**Related Clemco Literature**

Description	Stock No.
Contractor Series Catalog .....	21385
Abrasive Blasting Safety Practices .....	22090
Blast Off 2 .....	09294

**Options & Accessories**

Description	Stock No.
Coupling Gaskets (10) (for CFP and CFPM)* .....	08853
*Not included with the FHP. Nozzle washer serves as coupling gasket.	

**Color**  
Yellow

**Packaging**

Ships loose

**Dimensions**

Height: 2 1/2"  
Width (dia.): 3 3/8"  
Weight: .25 lb

(Dimensions are the same for all models)

Authorized Distributor:

ISO 9001:2008 certified. Clemco is committed to continuous product improvement. Specifications are subject to change without notice.